



Pond or Canal Sealing Instructions SOILFLOC® Sealant

If your ditch / pond / canal has water in it & is currently leaking, then now would be the best time to apply. The leak creates suction, drawing the polymers into the problem areas to seal the leaks.

Do not under apply. Determine in your leak is fast or slow. A slow leak is noticed over weeks/months. A fast leak is noticed over days/weeks.

Prepping for Application

Remove any deep silt, livestock, dense reeds or heavy vegetation, as they can impede the polymers ability to get to the outflows.

Soilfloc® Sealant Application

Simply sprinkled over the surface of the water. The water should not be moving and you should not apply during rain or wind events. Distribute it as if you are "feeding chickens" at the recommended rates. Remember to cast out gently no more than 5' by hand, scoop or fertilizer spreader from a small dingy or raft.

For Slow Leaks Apply

- 3 oz. per 11 sq. ft. applied as follows
 - SF Sealant Part A 1.5 oz. per 11 sq. ft.
 - SF Sealant Part B 1.5 oz. per 11 sq. ft.

For fast Leaks Apply

- 3.5 to 4 oz. per 11 sq. ft. applied as follows
 - SF Sealant Part A 1.75 - 2 oz. per 11 sq. ft.
 - SF Sealant Part B 1.75 - 2 oz. per 11 sq. ft.

Apply Soilfloc® Sealant Part A to approx. 11 sq. ft. section first followed immediately by Part B to the same 11 sq. ft. before moving to the next section.

If you have any questions please contact Sandra Miller @ 619-312-7777